

50 NB FLANGED THERMOWELL DIMENSIONS																																								
FLANGE RATING ANSI CLASS			GENERAL FLANGE DATA																																					
			O.D	THICKNESS	RAISED FACE		BOLT HOLES			RTJ GASKET																														
					O.D	HEIGHT	PCD	No.	SIZE	PCD																														
150			150	22	92	1.6	120.5	4	20	-																														
	300		165	28	92	1.6	127	8	20	-																														
		600	165	35	92	6.4	127	8	20	-																														
			215	51	124	8.0	165	8	26	95.25																														
			1500	215	124	8.0	165	8	26	95.25																														
S	U		<table border="1"> <thead> <tr> <th colspan="4">BOLTING</th> </tr> <tr> <th>ANSI RATING</th> <th>No.</th> <th>Dia.</th> <th>LENGTH</th> </tr> </thead> <tbody> <tr> <td>150</td> <td>4</td> <td>5/8"</td> <td>90</td> </tr> <tr> <td>300</td> <td>8</td> <td>5/8"</td> <td>100</td> </tr> <tr> <td>600</td> <td>8</td> <td>5/8"</td> <td>120</td> </tr> <tr> <td>900</td> <td>8</td> <td>7/8"</td> <td>160</td> </tr> <tr> <td>1500</td> <td>8</td> <td>7/8"</td> <td>165</td> </tr> </tbody> </table>										BOLTING				ANSI RATING	No.	Dia.	LENGTH	150	4	5/8"	90	300	8	5/8"	100	600	8	5/8"	120	900	8	7/8"	160	1500	8	7/8"	165
BOLTING																																								
ANSI RATING	No.	Dia.											LENGTH																											
150	4	5/8"											90																											
300	8	5/8"											100																											
600	8	5/8"											120																											
900	8	7/8"											160																											
1500	8	7/8"											165																											
102	55	-																																						
152	106	77																																						
229	182	153																																						
305	258	229																																						
381	334	305																																						
457	410	381																																						
610	563	534																																						